



### Main

Range of product	RM6
Product or component type	Gas insulated switchboard
Device composition	Fuse-switch 200 A
Network type	AC
Rated frequency (fr)	50/60 Hz
Rated voltage (Ur)	24 kV
Rated normal current (Ir)	630.0 A
Rated short-time withstand current (Ik)	20 kA rms 1 s
Extensibility	NE (not extensible)
Enclosure name	QI
Extensibility kit	Not provided
Function available	2 functions
Standards	IEC 62271-200

### Complementary

Bus rated current	630 A
Bushing type	Type C conforming to IEC Type C conforming to ANSI
Pressure sensor type	Standard manometer, < 1000 m, temperature-25...40 °C
User manual	English
IP degree of protection	IP67
IK degree of protection	IK07
Number of cables	1 x 25...300 mm <sup>2</sup> three core
Local signalling	voltage presence indicator light VPIS V2
Interlocking type	Without interlock
Type of operating handle	standard
Height	1142 mm
Width	829 mm
Depth	670 mm
Product weight	180 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Ambient air temperature for operation	-25...40 °C
Operating altitude	< 1000 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	200 kg
Package 1 Height	116 cm
Package 1 width	85 cm
Package 1 Length	71 cm